



Voltage Current Rating:1 AMP.30V AC
 Dielectric Withstanding Voltage:500V AC
 Contact Resistance:35 mΩ Max.
 Insulation Resistance:500MΩ Min.
 Temperature Range:-20℃ to +85℃

| 5 | BRACKET | STEEL | PLATING: Ni | |
|------|----------|-------------------------|---|--------------|
| 4 | COVER | LCP+30%GF | COLOR: BLACK | |
| 3 | HOUSING | PBT+30%GF | COLOR: BLACK | |
| 2 | SHELL | ZINC ALLOY | PLATING: Ni | |
| 1 | TERMINAL | COPPER ALLOY T=0.3mm | CONTACT AREA: G/F SOLDER AREA: Sn UNDER-PLATING: Ni | |
| ITEM | DESC. | MATERIAL | REMARKS | PART REMARKS |

| | | | | | | | | | | | | | |
|---|------------|--------|-------------|-----------------|-------------------|--------|---------------------------------------|-------|------------|----------|-----------|-----------------|-------------|
| △ | | | | QUALITY SYMBOLS | Tolerance | NAME: | SCSI 36P FEMALE 90度DIP 锌合金壳 (客户用图) | | | | PART NO. | B03-036618A7-01 | |
| △ | 2023/01/31 | 修正错误尺寸 | Jack Chen | □: ☒: | x. ±0.80 | REV: | A | UNIT: | mm | DRW BY | CHK BY | APP BY | DRAWING NO. |
| △ | 2015/05/12 | 新版发行 | Jack Chen | CRITICAL MAJOR | .x ±0.50 | SCALE: | N:1 | DATE: | 2015/05/12 | Huangmei | Jack Chen | | B03-004 |
| | SIDE | DATE | DESCRIPTION | APPROVER | ZERO DEFECT S.P.C | | | | | | | | |

| | | | | | | | |
|--|--|--|--|--|--|----------------------|---|
| | | | | | | 东莞市林诚塑胶电子有限公司 | http://www.lineconn.com TEL:0769-85181660 85181770 |
|--|--|--|--|--|--|----------------------|---|

8 7 6 5 4 3 2 1

F

E

D

C

B

A

F

E

D

C

B

A