



No. of Contact	A	B	C	D	E
09	16.92	24.99	30.81	18.80	15.3
15	25.25	33.32	39.14	26.90	23.6
25	38.80	47.04	53.04	40.30	37.2
37	55.45	63.50	69.32	56.95	53.75

**Voltage Current Rating: 1 AMP.**  
**Dielectric Withstanding Voltage: 500V AC**  
 Insulation Resistance: 500MΩ Min.  
 Temperature Range: -55°C to +105°C

PART NO:  
 B05-0XX1X1BN-S1

NO. OF CONTACT:  
 09 = 9 pos  
 15 = 15 pos  
 25 = 25 pos  
 37 = 37 pos

HOUSING COLOR:  
 1 = BLACK  
 5 = WHITE  
 6 = BLUE

ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS
5	SCREW	STEEL	PALTING: Ni	
4	REAR SHELL	SPCC	PALTING: Sn	
3	FRONT SHELL	SPCC	PALTING: Ni	
2	HOUSING/COVER	PBT+30%GF	COLOR: SEE PART NO.	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: G/F SOLDER AREA: Ni	

三件式

QUALITY SYMBOLS

□:    ☒:    △:    ▽:    ⊕:    ⊖:  
 CRITICAL    MAJOR    ZERO DEFECT    S.P.C

Tolerance

x.    ±0.80  
 .x    ±0.50  
 .xx    ±0.25

NAME:

D-SUB IDC压排式公头前锁4.8mm螺母  
 (客户用图)

REV:

A    UNIT: mm    DRW BY: Huangmei    CHK BY: Jack Chen    APP BY:    DRAWING NO. B05-123

SCALE:

N:1    DATE: 2022/04/08    Huangmei    Jack Chen    APP BY:    DRAWING NO. B05-123

lineconn 东莞市林诚塑胶电子有限公司    http://www.lineconn.com  
 TEL: 0769-85181660 85181770

△ 2022/04/08    NEW ISSUE    Jack Chen

SIDE    DATE    DESCRIPTION    APPROVER