



No. of Contact	A	B	C	D
15	16.3	25.0	30.8	19.3
26	24.6	33.3	39.1	27.5
44	36.3	47.0	53.0	41.3
62	54.8	63.5	69.3	57.7

Voltage Current Rating: 5 AMP.
 Dielectric Withstanding Voltage: 1000V AC
 Insulation Resistance: 1000MΩ Min.
 Temperature Range: -25°C to +85°C

PART NO: B04-0XX4X14N-02

NO.OF CONTACT:
 15 = 15 pos
 26 = 26 pos
 44 = 44 pos
 62 = 62 pos

HOUSING COLOR:
 1 = BLACK
 5 = WHITE
 6 = BLUE

4	REAR SHELL	SPCC	PALTING: Sn
3	FRONT SHELL	SPCC	PALTING: Ni
2	HOUSING	PBT+30%GF	COLOR: SEE PART NO.
1	TERMINAL	COPPER ALLOY	TERMINAL FINISH: FULL GOLD FINISHED 2u"
ITEM	DESC.	MATERIAL	REMAKS

△	2020/05/16	变更料号	Jack Chen
△	2020/05/11	依新料号编码原则变更料号	Jack Chen
△	2009/04/14	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER

QUALITY SYMBOLS		Tolerance	
□:	☒:	.x	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:		HD.D-SUB 车针母头焊线式通孔 (客户用图)				PART NO.		B04-0XX4X14N-01	
REV:	C	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.		
SCALE:	N:1	DATE:	2009/04/14	Huangmei	Jack Chen	B04-004			

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL: 0769-85181660 85181770