



技术参数:

1. 材料符合环保要求, 连接器对插符合IEC 61076-2-101
2. 连接器防护等级: IP67
3. 工作温度: -25~ +85° C
4. 机械寿命: >1000次插拔
5. 工作电压: 100V
6. 额定电流: 2A
7. 触点电阻: 10mΩ/Max

序号	名称	材料
7	12芯孔绝缘体	PPS
6	冲压孔	铜镀金
5	冲压孔	铜镀金
4	螺母	铜镀镍
3	垫片	不锈钢
2	锁紧弹簧	QBe1.9
1	插座壳体	锌合金镀镍

QUALITY SYMBOLS		Tolerance		NAME: HR10A-10R-12S(71) 12芯母座焊线式后锁面板		PART NO. B10-02PZ12SH-KGD	
□:	☒:	x.	±0.60	REV:	A	UNIT:	mm
CRITICAL	MAJOR	.x	±0.40	SCALE:	N:1	DATE:	2020/07/03
▽:	▽:	.xx	±0.25	DRW BY:	Huangmei	CHK BY:	Jack Chen
ZERO DEFECT	S.P.C					APP BY: DRAWING NO. B10-094	
				东莞市林诚塑胶电子有限公司 <a href="http://www.lineconn.com">http://www.lineconn.com</a>			
				TEL: 0769-85181660 85181770			

△	2020/07/03	NEW ISSUE	Jack Chen
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5