

技术参数:

1. 工作温度: $-25 \sim +85^{\circ} \text{C}$
2. 机械寿命: >500 次插拔
3. 额定电压: 250V
4. 额定电流: 4A


| 序号 | 名称 | 材料 |
|----|---------|--------|
| 7 | 12芯针绝缘体 | PPS |
| 6 | 端子 | 铜/镀金 |
| 5 | 端子 | 铜/镀金 |
| 4 | 螺母 | 铜镀镍 |
| 3 | 垫片 | 不锈钢 |
| 2 | 锁紧弹簧 | QBe1.9 |
| 1 | 插座壳体 | 锌合金 镀镍 |

QUALITY SYMBOLS

| | |
|-------------|-------|
| □: | ☒: |
| CRITICAL | MAJOR |
| ▽: | ▽: |
| ZERO DEFECT | S.P.C |

Tolerance

| | |
|-----|------------|
| x. | ± 0.60 |
| .x | ± 0.40 |
| .xx | ± 0.25 |



| | | | | | | | |
|--------|---------------------|-------|------------|----------|------------------|--------|-------------|
| NAME: | HR10A 10P-12P插板后锁面板 | | | PART NO. | B10-02PZ12SH-ZGD | | |
| REV: | A | UNIT: | mm | DRW BY | CHK BY | APP BY | DRAWING NO. |
| SCALE: | N:1 | DATE: | 2018/11/06 | Huangmei | Jack Chen | | B10-056 |

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
TEL:0769-85181660 85181770

| | | | |
|------|------------|-------------|------------|
| △ | 2018/05/26 | NEW ISSUE | 2018/11/06 |
| SIDE | DATE | DESCRIPTION | APPROVER |