



PCB LAYOUT

No.of Contact	A	B	C	D
09	16.30	25.00	30.80	11.08
15	24.80	33.30	39.20	19.39
25	38.30	47.04	53.04	33.24
37	54.80	63.50	69.40	49.86

Voltage Current Rating:5 AMP.
 Dielectric Withstanding Voltage:1000V AC
 Insulation Resistance:5000MΩ Min.
 Δ Temperature Range:-55°C to +105°C

PART NO:

B05-0XX6X1XD-02

NO.OF CONTACT:

- 09 = 9 pos
- 15 = 15 pos
- 25 = 25 pos
- 37 = 37 pos

HOUSING COLOR:

- 1 = BLACK
- 5 = WHITE
- 6 = BLUE

Δ TERMINAL PLATING:

- 4:FULL GOLD 2u"
- 5:FULL GOLD 1u"

5	SCREW	STEEL	PALTING:Ni	
4	BOARDLOCK	COPPER ALLOY	PALTING:Ni	
3	HOUSING	PBT+30%GF	COLOR:BLACK	
2	SHELL	SPCC	PALTING:Ni	
1	TERMINAL	COPPER ALLOY	CONTACT AREA: Au 2u" SOLDER AREA: Au 2u" UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

Δ	2019/11/04	Modified operating temperature	Huangmei	QUALITY SYMBOLS	Tolerance	NAME: D-SUB 车针母头90度插板, 铆合锁螺丝 (客户用图)				PART NO.	B05-0XX6X1XD-02		
Δ	2013/04/22	Added terminal plating types	JINGLI	□: ☒:	x. ±0.60	REV:	C	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
Δ	2011/06/14	NEW ISSUE	JINGLI	CRITICAL MAJOR	.x ±0.40	SCALE:	N:1	DATE:	2011/06/14	Huangmei	Jack Chen		B05-010
	SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽:	lineconn 东莞市林诚塑胶电子有限公司 http://www.lineconn.com							TEL:0769-85181660 85181770
					ZERO DEFECT S.P.C								