



High Power Current Rating:10,20 or 40 AMP.  
 High Power Current Resistance:2.7 Milliohms MAX.  
 Dielectric Withstanding Voltage:1000V AC  
 Insulation Resistance:5000MΩ Min.  
 Δ Temperature Range:-55°C to +105°C

PART NO:

B08-3W3411XN-X0

Δ Terminal Plating:

4 = Full Gold 2u"

5 = Full Gold 1u"

Current Rating:

A = 10 AMPS Dim.A φ1.70

B = 20 AMPS Dim.A φ2.80

C = 30 AMPS Dim.A φ3.30

D = 40 AMPS Dim.A φ4.60

4	REAR SHELL	SPCC	PALTING: Sn	
3	FRONT SHELL	SPCC	PALTING: Ni	
2	HOUSING	PBT+30%GF	COLOR: BLACK	
1	TERMINAL	COPPER ALLOY	PALTING: SEE PART NO.	
ITEM	DESC.	MATERIAL	REMAKS	PART REMAKS

Δ	2023/08/17	1.Added the terminal plating type 2.Modified operating temperature	Jack Chen
Δ	2013/03/11	NEW ISSUE	JINGLI
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□ :	☒ :	x.	±0.60
CRITICAL	MAJOR	.x	±0.40
▽ :	▽ :	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:		3W3母头焊线式光孔POWER D-SUB (客户用图)			PART NO.	B08-3W3411XN-X0		
REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2013/03/11	Huangmei	Jack Chen		B08-006	
				东莞市林诚塑胶电子有限公司			<a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL:0769-85181660 85181770	
8	7	6	5	4	3	2	1	