



PCB Layout (B2)

• ELECTRICAL CHARACTERISTICS

- Contact Current Rating: 1 Amp
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance: 500MΩ/Min
- Contact Resistance: 35mΩ/Max
- Operation Temperature: -25°C ~ +85°C

4	BRACKET	ZINC ALLOY	PLATING: Ni	
3	HOUSING	PBT+G.F.30% (UL 94V-0)	COLOR: BLACK	
2	SHELL	SPCC	PLATING: Ni	
1	TERMINAL	PHOSPHOR BRONZE	CONTACT AREA: Au 5u" SOLDER AREA: Sn UNDER-PLATING: Ni	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

△				QUALITY SYMBOLS
△				□: ☒:
△	2016/07/19 新版发行		King Zhou	CRITICAL MAJOR
SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽: ZERO DEFECT S.P.C
8	7	6	5	

Tolerance		NAME: SCSI PIN TYPE 68P MALE 180° DIP (客户用图)		PART NO.	B02-068711EN-1S	
x.	±0.80	REV:	A	UNIT:	mm	DRW BY
.x	±0.50	SCALE:	N:1	DATE:	2016/07/19	JACK CHEN
.xx	±0.30					DEAN FAN
		APP BY		DRAWING NO.		
				B02-057		
Lineconn 东莞市林诚塑胶电子有限公司				http://www.lineconn.com		
				TEL:0769-85181660 85181770		
4	3	2	1			