



P.C.B LAYOUT

No. of Contact	A ±0.25 ±.010	B ±0.13 ±.005	C ±0.38 ±.015	D ±0.25 ±.010
15	16.30	25.00	30.80	19.28
26	24.80	33.30	39.20	27.51
44	38.30	47.04	53.04	41.28
62	54.80	63.50	69.30	57.71

Voltage Current Rating:5 AMP.  
 Dielectric Withstanding Voltage:1000V AC  
 Insulation Resistance:1000MΩ Min.  
 Temperature Range:-55℃ to +105℃

PART NO: B04-0XX8X1XD-02

No.of contact:  
 15:15 pos  
 26:26 pos  
 44:44 pos  
 62:62 pos  
 Housing color:  
 1:Black  
 5:White  
 6:Blue  
 Terminal plating:  
 4:Full gold 2u"  
 5:Full gold 1u"

ITEM	DESC.	MATERIAL	REMARKS
6	SCREW	STEEL	PALTING: Ni
5	BOARDLOCK	COPPER ALLOY	PALTING: Ni
4	HOUSING	PBT+30%GF	COLOR: SEE PART NO.
3	REAR SHELL	SPCC	PALTING: Sn
2	FRONT SHELL	SPCC	PALTING: Ni
1	TERMINAL	COPPER ALLOY	PALTING: SEE PART NO.

SIDE	DATE	DESCRIPTION	APPROVER
△	2021/08/13	NEW ISSUE	Jack Chen

QUALITY SYMBOLS	Tolerance
□: CRITICAL ▽: ZERO DEFECT	x. ±0.60 .x ±0.40 .xx ±0.25

NAME:	HD. D-SUB 车针母头180度直插, 后铆6.0铜柱, 前锁4.8螺母	PART NO.	B04-0XX8X1XD-02				
REV:	A	UNIT:	mm	DRW BY:	CHK BY:	APP BY:	DRAWING NO.
SCALE:	N:1	DATE:	2021/08/13	Huangmei	Jack Chen		B04-062

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>  
 TEL:0769-85181660 85181770