



- 技术参数:
1. 材料符合环保要求, 连接器对插符合IEC 61076-2-101
  2. 连接器防护等级: IP67
  3. 工作温度: -25~ +85° C
  4. 机械寿命: >1000次插拔
  5. 工作电压: 100V
  6. 额定电流: 2A
  7. 触点电阻: 10mΩ/Max

|    |      |        |
|----|------|--------|
| 7  | 胶芯   | PPS    |
| 6  | 端子   | 铜镀金    |
| 5  | 端子   | 铜镀金    |
| 4  | 螺母   | 铜镀镍    |
| 3  | 垫片   | 不锈钢    |
| 2  | 锁紧弹簧 | QBe1.9 |
| 1  | 插座壳体 | 锌合金镀镍  |
| 序号 | 名称   | 材料     |

|      |  |      |             |                 |           |           |                                 |     |       |            |                         |                  |        |             |
|------|--|------|-------------|-----------------|-----------|-----------|---------------------------------|-----|-------|------------|-------------------------|------------------|--------|-------------|
|      |  |      |             | QUALITY SYMBOLS | Tolerance | NAME:     | HR10A-10R-10S (72) 10芯母座焊线式后锁面板 |     |       |            | PART NO.                | B10-02PZ10SH-KGD |        |             |
|      |  |      |             | □: CRITICAL     | ☒: MAJOR  | x. ±0.60  | REV:                            | A   | UNIT: | mm         | DRW BY                  | CHK BY           | APP BY | DRAWING NO. |
| A    |  |      |             | △: ZERO DEFECT  | ▽: S.P.C  | .x ±0.40  | SCALE:                          | N:1 | DATE: | 2022/01/09 | Huangmei                | Jack Chen        |        | B10-106     |
|      |  |      |             |                 |           | .xx ±0.25 | lineconn 东莞市林诚塑胶电子有限公司          |     |       |            | http://www.lineconn.com |                  |        |             |
|      |  |      |             |                 |           |           | TEL:0769-85181660 85181770      |     |       |            |                         |                  |        |             |
| SIDE |  | DATE | DESCRIPTION | APPROVER        |           |           |                                 |     |       |            |                         |                  |        |             |
| 8    |  | 7    | 6           | 5               | 4         |           | 3                               |     | 2     |            | 1                       |                  |        |             |