

RoHS



Diagram illustrating the cross-section of a 10-core optical fiber. The central core is labeled P1 and P2. The surrounding cores are labeled 1 through 8 and SHELL. The cores are arranged in a circular pattern around the central core.

Core Label	Core Color/Label
P1	ORANGE/WHITE
1	ORANGE
2	GREEN/WHITE
3	GREEN
6	BLUE
4	BLUE/WHITE
5	BROWN/WHITE
7	BROWN
8	BRAID
SHELL	

型号	线材规格	长度 (dm)
A10-00811XXX-B1	黑色普通线4P*24AWG OD 6.0mm	XXX:001=1dm XXX:010=10dm
A10-00811XXX-B2	黑色拖链线4P*24AWG OD 6.0mm	
A10-00813XXX-B1	绿色普通线4P*24AWG OD 6.0mm	
A10-00813XXX-B2	绿色拖链线4P*24AWG OD 6.0mm	
A10-00811XXX-C2	黑色拖链线4P*26AWG OD 6.0mm	
A10-00818XXX-C1	黄色普通线4P*26AWG OD 6.5mm	

1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
2. CONDUCTOR RESISTANCE: 5 OHMS MAX.
3. INSULATOR RESISTANCE: 1M OHMS MIN, DC 300V 0.01sec.
4. THIS PRODUCT MEET ROHS STANDARD ENVIRONMENTAL PROTECTION POLICY.

4	外模	PVC 45P	NA
3	内模	LDPE,Transparent	NA
2	连接器	RJ45 8P8C连接器,带屏蔽壳	2PCS
1	线材	千兆工业网线4P,双屏蔽(其他参数见料号规格说明)	NA
ITEM	PART NAME	DESCRIPTION	QY'T

				QUALITY SYMBOLS □ : ▣ : CRITICAL MAJOR ▽ : ▽ : ZERO DEFECT S.P.C	Tolerance		NAME:	千兆工业网线成型式				PART NO.		A10-0081X XXX-XX		
					尺寸(MM)	公差(MM)	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.		
	2020/04/08	新版发行	Jack Chen		300~2000	±50	SCALE:	NONE	DATE:	2020/04/08	Huangmei	Jack Chen				
					2001~5000	±100									5001~	±150
SIDE	DATE	DESCRIPTION	APPROVER		 东莞市林诚塑胶电子有限公司								http://www.lineconn.com TEL:0769-85181660 85181770			

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
TEL:0769-85181660 85181770