



No. of Contact	A	B	C	D
09	16.33	24.99	30.81	19.0
15	24.66	33.32	39.14	27.7
25	38.38	47.04	53.04	41.0
37	54.84	63.50	69.32	57.3

Current rating: 3 AMP
 Withstanding voltage: 1000V AC
 Insulation resistance: 1000mΩ min.
 Temperature range: -55°C to +125°C
 Durability: 500 cycles
 ROHS compliant

Part No.: B05-0XX8X1AD-E5
 Pin No.:
 09: 9pin
 15: 15pin
 25: 25pin
 37: 37pin
 Housing:
 1: black
 5: white
 6: blue

6	Screw	Steel	Palting: Ni
5	Boardlock	Copper alloy	Palting: Ni
4	Housing	PBT+30%GF	Color: see part no.
3	Rear shell	SPCC	Palting: Sn
2	Front shell	SPCC	Palting: Ni
1	Terminal	Copper alloy	Contact area: G/F Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remarks

△	2014/09/02	First edition release	King Zhou
SIDE	DATE	DESCRIPTION	APPROVER

QUALITY SYMBOLS		Tolerance	
□:	☒:	.x	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECTS.P.C			

NAME:	D-SUB female vertical, rear riveted copper post, front lock 5.8mm screw			PART NO.	B05-0XX8X1AD-E5		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2014/09/02	Jing Li	King Zhou		B05-091

Lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL: 0769-85181660 85181770

8 7 6 5 4 3 2 1

8 7 6 5 4 3 2 1