



Rated current: 0.50A/contact  
 Insulation resistance: 500mohm min.  
 Withstanding voltage: 250V AC for 1 minute.  
 Operating temperature: -25°C to +105°C  
 ROHS compliant

Item	Desc.	Material	Remark
5	Board lock	Copper alloy	Plated Ni
4	Screws	Copper alloy	Plated Ni
3	Housing	LCP+30%G.F.	Color: black
2	Shell	SPCC	Plating: Ni
1	Terminal	Copper alloy	Contact area: plated G/F Solder area: plated Tin Under-plated: Ni

SIDE	DATE	DESCRIPTION	APPROVER
△	2024/03/26	Changed electrical properties	Jack Chen
△	2024/03/20	Increase in iron casing fastening points	Jack Chen
△	2019/04/23	First edition release	Jack Chen

QUALITY SYMBOLS		Tolerance	
□:	☒:	.x	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:	VHDCI 68pin female vertical for PCB			PART NO.	B06-068811AA-01		
REV:	C	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2019/04/23	Huangmei	Jack Chen		B06-031
				<b>Lineconn 东莞市林诚塑胶电子有限公司</b> <a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL:0769-85181660 85181770			