



A-A section

Hood A

Hood B

Current rating:1A
Contact resistance:35mΩ max.
Withstanding voltage:500V AC
Insulation resistace:500mΩ Min.
Temperature range:-45℃ to +105℃
ROHS compliant

8	Hood	ABS	Color: gray
7	Cable clip	Steel	Plating: Ni
6	Screw	Steel	Plating: Ni
5	Spring latch	Stainless steel	
4	Cover	PBT+30%GF	Color: black
3	Housing	PBT+30%GF	Color: black
2	Shell	SPCC	Plating: Ni
1	Terminal	Copper alloy	Contact area: Au 3u" Solder area: G/F Under-plating: Ni
Item	Desc.	Material	Remaks

A	△	2013/04/16	Change BOM	King Zhou	QUALITY SYMBOLS □: ☒: CRITICAL MAJOR ▽: ▽: ZERO DEFECT S.P.C	Tolerance .x ±0.60 .x ±0.40 .xx ±0.25	NAME: PCR-20F 20pin female solder conn.				PART NO.		B01-02042134-01	
	△	2013/04/13	Modify the mold, Adjust dimensional	King Zhou			REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
	△	2013/01/09	First edition release	King Zhou			SCALE:	N:1	DATE:	2013/01/09	Huangmei	King Zhou		B01-009
	SIDE	DATE	DESCRIPTION	APPROVER			lineconn		东莞市林诚塑胶电子有限公司			http://www.lineconn.com TEL:0769-85181660 85181770		