



Voltage current rating: 5 AMP.
Dielectric withstanding voltage: 500V AC
Contact resistance: 30 mΩ Max.
Insulation resistance: 500MΩ Min.
Temperature range: -20℃ to +85℃
ROHS compliant
Waterproof rating: IP67

8	Gland nut	Synthetic rubber	Color: black	1pcs
7	Bushing	Synthetic rubber	Color: black	1pcs
6	Hood	Synthetic rubber	Color: black	1pcs
5	Socket insulator	Synthetic rubber	Color: black	1pcs
4	Card	Synthetic rubber	Color: blue	1pcs
3	Terminal	Copper alloy	Plating: G/F	2pcs
2	Screw	Steel	Plating: Ni	2pcs
1	Gasket	Synthetic rubber	Color: black	1pcs
Item	Desc.	Material	Remarks	Part remarks

				QUALITY SYMBOLS	Tolerance	NAME:	JN4FT02SJ1-R,J3/J4 2pin waterproof connector for Mitsubishi servo motor				PART NO.	B01-00211154-01			
	2021/03/27	Change part number	Shuo Cao	☐ : ☒ :	x. ±0.60 .x ±0.40 .xx ±0.25	REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.		
	2019/10/09	First edition release	King Zhou	CRITICAL MAJOR		SCALE:	N:1	DATE:	2019/10/09	Huangmei	Shuo Cao		B01-027		
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C		lineconn 东莞市林诚塑胶电子有限公司								http://www.lineconn.com TEL:0769-85181660 85181770	