








Termination cover
(1 places)



Wire holder
(2 places 0.75,0.90)



Wire holder
(2 places 0.62)

Current rating: 1A
Contact resistance: 35mΩ max.
Dielectric withstanding voltage: 500V AC
Insulation resistance: 500MΩ Min.
Temperature range: -45℃ to +125℃
ROHS compliant
Part No.:

B03-02611E0-X0

Wire holder: _____
28AWG or 30AWG wire
6: 0.62mm
7: 0.75mm
9: 0.90mm

4	Cover	PBT+G.F.30% (UL 94V-0)	Color:black
3	Housing	PBT+G.F.30% (UL 94V-0)	Color:black
2	Shell	SPCC	Plating:Ni
1	Terminal	Phosphor bronze	Contact area:Au 5u" Solder area:Sn Under-plating:Ni
Item	Desc.	Material	Remark

				QUALITY SYMBOLS	Tolerance		NAME:		SCSI 26pin male IDC assembly conn.				PART NO.		B03-026111E0-X0	
	2024/07/29	Add 0.75mm, 0.90mm wire holder dwg	Jack Chen	:	x.	±0.60	REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.		
	2008/08/12	First edition release	King Zhou	CRITICAL MAJOR	.x	±0.40	SCALE:	N:1	DATE:	2008/08/12	Huangmei	Jack Chen		B03-055		
				:	.xx	±0.25	东莞市林诚塑胶电子有限公司					http://www.lineconn.com				
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C								TEL:0769-85181660 85181770				