


PCB layout(14,26,50pin)



PCB layout(20,36pin)

No.of contacts:	A	B	C
14	18.4	13.90	7.62
20	22.0	18.00	11.43
26	25.8	21.60	15.24
36	32.2	28.00	21.59
50	41.1	36.80	30.48

Current rating: 1 AMP.
Withstanding voltage: 500V AC
Insulation resistance: 500M Ω Min.
Contact resistance: 35m Ω max.
Temperature range: -45 $^{\circ}$ C to +125 $^{\circ}$ C
ROHS compliant

Part number: B01-0XX711AN-20

No.of contacts: _____

14: 14pin
20: 20pin
26: 26pin
36: 36pin
50: 50pin

3	Housing	PBT+G.F.30% (UL 94V-0)	Color:black
2	Shell	SPCC	Plating:Ni
1	Terminal	Phosphor bronze	Contact area:G/F Solder area:Sn Under-plating:Ni
Item	Desc.	Material	Remark

	2025/09/03	First edition release	Carl Hu
SIDE	DATE	DESCRIPTION	APPROVER

QUALITY SYMBOLS		Tolerance	
		x.	± 0.60
CRITICAL	MAJOR	.x	± 0.40
		.xx	± 0.25
ZERO DEFECT	S.P.C		

NAME:		SM(SCSI) male vertical for PCB			PART NO.		B01-0XX711AN-20	
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2025/09/03	Huangmei	Carl Hu		B01-091	
lineconn 东莞市林诚塑胶电子有限公司					http://www.lineconn.com			
					TEL:0769-85181660 85181770			