









L type



S type



PCB layout

Current rating: 1 AMP.
Withstanding voltage: 500V AC
Insulation resistance: 500M Ω min.
Contact resistance: 35m Ω Max
Temperature range: -55 $^{\circ}$ C to +125 $^{\circ}$ C
ROHS compliant

Part number:
B02-026818EC-1X
Bracket finishes: _____
L: latch bracket
S: screw bracket

3	Housing	PBT+30%GF	Color: black, UL94V-0
2	Shell	Zinc alloy	Plating: Ni
1	Terminal	Phosphor bronze	Contact area: Au 5u" Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remark

△	2021/07/14	Change part number	Jack Chen
△	2008/08/11	Change tolerance	Jack Chen
△	2008/07/04	First edition release	Jack Chen


SIDE	DATE	DESCRIPTION	APPROVER
------	------	-------------	----------

QUALITY SYMBOLS

□:	☒:
CRITICAL	MAJOR
▽:	▽:
ZERO DEFECT	S.P.C

Tolerance

.x	±0.60
.x	±0.40
.xx	±0.25



NAME:	SCSI II (HPDB) 26pin female vertical with bracket for PCB				PART NO.	B02-026818EC-1X		
REV:	C	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO. B02-001	
SCALE:	N:1	DATE:	2008/07/04	Huangmei	Jack Chen			