

No. of contact	A	B	C	D	E	F
15	16.92	24.99	30.81	18.9	2.29	1.145
26	25.25	33.32	39.20	27.5	2.29	1.145
44	38.96	47.04	53.05	41.3	2.29	1.145
62	55.42	63.50	69.40	57.7	2.41	1.205

▲ Current rating: 3A
 Withstanding voltage: 1000V AC
 Insulation resistance: 1000MΩ Min.
 Temperature range: -45℃ to +105℃
 ROHS compliant

Part number: B04-0XX31A0-SD

No.of contact:_____

15: 15pos

26: 26pos

44: 44pos

62: 62pos

Housing color:_____

1: Black

5: White

6: Blue

6	Nut	Steel	Palting: Ni
5	Rear shell	SPCC	Palting: Sn
4	Front shell	SPCC	Palting: Ni
3	Rear hsg	PBT+30%GF	Color: see part no.
2	Front hsg	PBT+30%GF	Color: see part no.
1	Terminal	Copper alloy	Contact area: G/F Solder area: Sn
Item	Desc.	Material	Remarks

	2023/06/24	Changed electrical properties	Jack Chen	QUALITY SYMBOLS □: ✕: CRITICAL MAJOR ▽: ▽: ZERO DEFECT S.P.C	Tolerance		NAME:		HD.D-SUB male solder,two-piece housing, rivet 4.0 through hole nuts at the rear				PART NO.		B04-0XX3X1A0-SD	
	2023/06/16	Add dimension	Jack Chen		x. ±0.60	REV:	D	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO. B04-020			
	2016/08/11	First edition release	Jing Li		.x ±0.40	SCALE:	N:1	DATE:	2016/08/11	Huangmei	Jack Chen					
SIDE	DATE	DESCRIPTION	APPROVER		.xx ±0.25	 								lineconn 东莞市林诚塑胶电子有限公司 http://www.lineconn.com TEL:0769-85181660 85181770		