


Termination Cover
(1 Places)



Wire Holder
(2 Places)

Current rating: 1A. 30V AC
Insulation resistance: 500MΩ/Min
Withstanding voltage: 500V AC/Min
Contact resistance: 35mΩ Max
Temperature range: -45℃ to +125℃
ROHS compliant

Part number: B02-100111E0-X0

Wire holder:
28AWG or 30AWG wire
6: 0.62mm
7: 0.75mm
9: 0.90mm

4	Cover	PBT+G.F.30% (UL 94V-0)	Color: black
3	Housing	PBT+G.F.30% (UL 94V-0)	Color: black
2	Shell	SPCC	Plating: Ni
1	Terminal	Phosphor bronze	Contact area: Au 5u" Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remark

△	2021/06/03	Modify incorrect part number	Carl Hu
△	2020/11/13	Change tolerance	Carl Hu
△	2016/07/19	First edition release	King Zhou

QUALITY SYMBOLS	
□:	☒:
CRITICAL	MAJOR
▽:	▽:
ZERO DEFECT	S.P.C

Tolerance	
x.	±0.60
.x	±0.40
.xx	±0.25

NAME:		SCSI II(HPDB) 100pin male IDC assembly connector			PART NO.	B02-100111E0-X0	
REV:	D	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2016/07/19	Yugong	Carl Hu		B02-067
lineconn 东莞市林诚塑胶电子有限公司					http://www.lineconn.com TEL:0769-85181660 85181770		

SIDE	DATE	DESCRIPTION	APPROVER
------	------	-------------	----------