



Wire holder
(2 places)

Current rating:1A
Withstanding voltage:500V AC
Contact resistance : 35mΩ max.
Insulation resistance:500MΩ Min.
Temperature range:−45℃ to +105℃
ROHS compliant
Part number:

B03-100111E0-X0

Wire holder: _____
28AWG or 30AWG wire
6: 0.62mm
7: 0.75mm
9: 0.90mm


 东莞市林诚塑胶电子有限公司
 <http://www.lineconn.com>
 TEL:0769-85181660 85181770

△	2022/10/09	Add ROHS requirements	Carl Hu	QUALITY SYMBOLS	Tolerance	NAME:	SCSI(HPCN) 100pin male IDC assembly type connector				PART NO.	B03-100111E0-X0	
△	2021/07/02	Change part number	Carl Hu	□: ☒:	x. ±0.60	REV:	F	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2012/08/24	First edition release	King Zhou	CRITICAL MAJOR	.x ±0.40	SCALE:	N:1	DATE:	2012/08/24	Yugong	Carl Hu		B03-078
				▽: ▽:	.xx ±0.25	 东莞市林诚塑胶电子有限公司					http://www.lineconn.com		
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT S.P.C							TEL:0769-85181660 85181770		

lineconn 东莞市林诚塑胶电子有限公司