



PCB LAYOUT

High Power Contact Current Rating:  
10,20 or 40AMPS  
High Power Contact Resistance:  
2.7 Milliohms Max.  
Dielectric Withstanding Voltage:  
1000V AC For 1 Minute  
Insulation Resistance:5000MΩ Min.  
Temperature Range:-25°C to +85°C

PART NO:  
B08-AW26X14D-X1

HOUSING COLOR:  
1:BLACK  
3:GREEN  
5:WHITE

CURRENT RATING:  
A = 10 AMPS Dim.A  $\phi$ 1.7 Dim.B  $\phi$ 2.2  
B = 20 AMPS Dim.A  $\phi$ 2.8 Dim.B  $\phi$ 3.3  
C = 30 AMPS Dim.A  $\phi$ 3.2 Dim.B  $\phi$ 3.7  
D = 40 AMPS Dim.A  $\phi$ 3.7 Dim.B  $\phi$ 4.2

6	JACKSCREWS	BRASS	PLATING: Ni	
5	HOUSING	PBT+30%GF	COLOR: WHITE	
4	RIVETED INSERT	BRASS	PLATING: Ni	
3	REAR SHELL	SPCC	PLATING: Sn	
2	FRONT SHELL	SPCC	PLATING: Ni	
1	TERMINAL	BRASS	TERMINAL FINISH: FULL GOLD FINISHED 2u"	
ITEM	DESC.	MATERIAL	REMARKS	PART REMARKS

				QUALITY SYMBOLS	Tolerance	NAME:	17W2 90度母头柳支架鱼叉锁螺丝 POWER D-SUB (客户用图)				PART NO.	B08-AW26114D-X1	
				□:    ☒:	.x    ±0.50	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
				CRITICAL MAJOR	.x    ±0.30	SCALE:	N:1	DATE:	2017/05/13	JINGLI	KING ZHOU		B08-048
				▽:    ▽:	.xx    ±0.25	东莞市林诚塑胶电子有限公司 <a href="http://www.lineconn.com">http://www.lineconn.com</a> TEL: 0769-85181660 85181770							
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECTS.P.C									

8 7 6 5 4 3 2 1

F  
E  
D  
C  
B  
A

F  
E  
D  
C  
B  
A

8 7 6 5 4 3 2 1