



Notes:
 1.Electrical test:100% open,short&miss wire test.
 2.Conductor resistance:5 ohms max.
 3.Insulator resistance: 1m ohms min, dc 300v 0.01sec.
 4.ROHS compliant
 5.Part no. description: A06-02011XXX-A3,
 XXX:001=length:10cm

6	Copper foil	Copper foil	NA
5	Screw	Big E32.7 22 balck M2.6	4PCS
4	Mold	Black PVC 45P	NA
3	Mold	LD-PE	NA
2	Connector	HPCN 20pin male solder molded type,houing color:black	2PCS
1	Cable	UL20276 10P*28AWG+AL+braid,PVC jacket,color black,OD: 7.0	1PCS
Item	Part name	Description	QY'T

QUALITY SYMBOLS

□: ☒:
 CRITICAL MAJOR
 ▽: ▽:
 ZERO DEFECT S.P.C

Tolerance

Length(mm)	Tolerance(mm)
300~2000	±50
2001~5000	±100
5001~	±150

NAME:	SCSI 20pin male to male cable,molded type with screw			PART NO.	A06-02011XXX-A3		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	NONE	DATE:	2024/09/28	Lei Fan	Jack Chen		A06-011

lineconn 东莞市林诚塑胶电子有限公司

http://www.lineconn.com
 TEL:0769-85181660 85181770

△	2024/09/28	First edition release	Jack Chen
SIDE	DATE	DESCRIPTION	APPROVER

8 7 6 5 4 3 2 1