



Current rating: 1 AMP.
Withstanding voltage: 500V AC
Insulation resistance: 500MΩ Min.
Contact resistance: 35mΩ max.
Temperature range: -45℃ to +125℃
ROHS compliant
Part number:
B02-036111E0-X0
Wire holder:
28AWG or 30AWG wire
6: 0.62mm
7: 0.75mm
9: 0.90mm

Termination cover
(1 places)

Wire holder
(2 places)

4	Cover	PBT+G.F.30% (UL 94V-0)	Color: black
3	Housing	PBT+G.F.30% (UL 94V-0)	Color: black
2	Shell	SPCC	Plating: Ni
1	Terminal	Phosphor bronze	Contact area: Au 5u" Solder area: Ni Under-plating: Ni
Item	Desc.	Material	Remark

△	2021/06/29	Change part number	Carl Hu
△	2017/09/04	Add 0.9mm wire holder	King Zhou
△	2010/06/24	First edition release	King Zhou

QUALITY SYMBOLS
□: ☒:
CRITICAL MAJOR
▽: ▽:
ZERO DEFECT S.P.C

Tolerance	
x.	±0.60
.x	±0.40
.xx	±0.25

NAME:	SCSI II(HPDB) 36pin male IDC connector assembly type				PART NO.	B02-036111E0-X0		
REV:	E	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	N:1	DATE:	2010/06/24	Huangmei	Carl Hu		B02-039	

SIDE	DATE	DESCRIPTION	APPROVER	lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com		TEL:0769-85181660 85181770
------	------	-------------	----------	------------------------	--	-------------------------	--	----------------------------