






Termination cover
(1 places)



Wire holder
(2 places)

Current rating: 1 AMP.
Withstanding voltage: 500V AC
Insulation resistance: 500M Ω Min.
Contact resistance: 35m Ω max.
Temperature range: -45 $^{\circ}$ C to +125 $^{\circ}$ C
ROHS compliant
Part number:
B02-026111E0-X0
Wire holder:
28AWG or 30AWG wire
6: 0.62mm
7: 0.75mm
9: 0.90mm

4	Cover	PBT+G.F.30% (UL 94V-0)	Color:black
3	Housing	PBT+G.F.30% (UL 94V-0)	Color:black
2	Shell	SPCC	Plating:Ni
1	Terminal	Phosphor bronze	Contact area:Au 5u" Solder area:Ni Under-plating:Ni
Item	Desc.	Material	Remark

	2021/08/04	Change part number	Carl Hu
	2017/09/04	Add 0.9mm wire holder	King Zhou
	2008/08/12	First edition release	King Zhou

QUALITY SYMBOLS	
CRITICAL	MAJOR
ZERO DEFECT	S.P.C

Tolerance	
x.	± 0.60
.x	± 0.40
.xx	± 0.25

NAME:		SCSI II(HPDB) 26pin male IDC connector assembly type			PART NO.	B02-026111E0-X0	
REV:	D	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2008/08/12	Huangmei	Carl Hu		B02-028
lineconn 东莞市林诚塑胶电子有限公司					http://www.lineconn.com TEL:0769-85181660 85181770		