



Wire Assignment:

P1	P2	P1	P2
2	25	9	18
15	12	22	5
3	24	10	17
16	11	23	4
4	23	11	16
17	10	24	3
5	22	12	15
18	9	25	2
6	21	1	Drain
19	8	14	Drain
7	20	13	Drain
20	7	26	Drain
8	19	Shell	Braid
21	6		Shell

Notes:

- 1.Electrical test:100% open,short&miss wire test.
- 2.Conductor resistance:5 ohms max.
- 3.Insulator resistance: 1m ohms min, dc 300v 0.01sec.
- 4.ROHS compliant
- 5.Part no. description: A10-02611XXX-05, XXX: 001=length: 10cm

Item	Material	Description	Qty	Unit
①	Cable	UL20276(1P*28AWG+AL)x11C+28AWG*2C+28AWG drain*4C+AB OD:9.5mm,color: black,flexible cable	N/A	mm
②	Conn	MDR 26pin male solder	1	PCS
③	Conn	SDR 26pin male solder	1	PCS
④	Inner Mold	LD-PE	N/A	KG
⑤	Over Mold	45P PVC,black	N/A	KG
⑥	Copper Foil	Copper Foil	N/A	mm
⑦	Screw	M2.6 screw	2	PCS
⑧	Screw	M2.0 screw	2	PCS

△			
△	2022/04/26	Develop a new set of molds and change the shape	Jack Chen
△	2021/03/09	First edition release	Jack Chen
SIDE	DATE	DESCRIPTION	APPROVER

QUALITY SYMBOLS

□:	☒:
CRITICAL	MAJOR
▽:	▽:
ZERO DEFECT	S.P.C

Tolerance	
Length(mm)	Tolerance(mm)
300~2000	±50
2001~5000	±100
5001~	±150

NAME:	Camera Link MDR-SDR cable,four ground				PART NO.	A10-02611XXX-05		
REV:	B	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.	
SCALE:	NONE	DATE:	2021/03/09	Qiang Liao	Jack Chen		A10-033	
lineconn 东莞市林诚塑胶电子有限公司					http://www.lineconn.com			
					TEL:0769-85181660 85181770			