



Pin assignment

P1 P2

01 ———— 01
 02 ———— 02
 03 ———— 03
 04 ———— 04
 05 ———— 05
 06 ———— 06
 07 ———— 07
 08 ———— 08
 09 ———— 09
 Shell ———— Shell

Current rating: 3A
 Withstanding voltage: 500V AC
 Contact resistance : 35mΩ max.
 Insulation resistance: 500MΩ Min.
 Temperature range: -45°C to +105°C
 Label: yellow color with black character
 ROHS compliant

| 5 | Screw | Steel | Plating: Ni |
|------|------------|------------------------|---|
| 4 | connecting | SPCC | Plating: Ni |
| 3 | Housing | PBT+G.F.30% (UL 94V-0) | Color: blue |
| 2 | Shell | SPCC | Plating: Ni |
| 1 | Terminal | Copper alloy | Contact area: G/F Solder area: Sn Under-plating: Ni |
| Item | Desc. | Material | Remark |

| △ | 2022/04/08 | Change tolerance | Carl Hu |
|------|------------|-----------------------|-----------|
| △ | 2022/03/24 | Change tolerance | Carl Hu |
| △ | 2011/12/18 | First edition release | Jack Chen |
| SIDE | DATE | DESCRIPTION | APPROVER |
| 8 | 7 | 6 | 5 |

| QUALITY SYMBOLS | | Tolerance | |
|-----------------|-------|-----------|-------|
| □ : | ☒ : | .x | ±0.60 |
| CRITICAL | MAJOR | .x | ±0.40 |
| ▽ : | ▽ : | .xx | ±0.25 |
| ZERO DEFECT | S.P.C | | |

| | | | | | | | | | |
|--------|---|-------|------------|-------------------------------|----------|-----------------|-------------|--|---|
| NAME: | MINI GENDER CHANGER D-SUB 9pin male to female adaptor | | | | PART NO. | C05-009361AD-01 | | | |
| REV: | E | UNIT: | mm | DRW BY | CHK BY | APP BY | DRAWING NO. | | |
| SCALE: | N:1 | DATE: | 2011/12/18 | Huangmei | Carl Hu | | C05-002 | | |
| | | | | lineconn 东莞市林诚塑胶电子有限公司 | | | | | http://www.lineconn.com TEL:0769-85181660 85181770 |

F
E
D
C
B
A

F
E
D
C
B
A

8 7 6 5 4 3 2 1

8 7 6 5 4 3 2 1