



Pin assignment

P1	P2
01	01
02	02
03	03
04	04
05	05
06	06
07	07
08	08
09	09
Shell	Shell

Current rating: 3A
 Withstanding voltage: 500V AC
 Contact resistance : 35mΩ max.
 Insulation resistance: 500MΩ Min.
 Temperature range: -45°C to +105°C
 Label: yellow color with black character
 ROHS compliant

Item	Desc.	Material	Remark
5	Screw	Steel	Plating: Ni
4	connecting	SPCC	Plating: Ni
3	Housing	PBT+G.F.30% (UL 94V-0)	Color: blue
2	Sheel	SPCC	Plating: Ni
1	Terminal	Copper alloy	Contact area: G/F Solder area: Sn Under-plating: Ni

△	2021/09/21	Change tolerance	Carl Hu
△	2021/06/04	Change part number	Carl Hu
△	2014/08/18	First edition release	Jack Chen
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□ :	☒ :	x.	±0.60
CRITICAL	MAJOR	.x	±0.40
▽ :	▽ :	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:		PART NO.	
MINI GENDER CHANGER D-SUB 9pin female to female adaptor		C05-009261AD-01	
REV:	C	UNIT:	mm
SCALE:	N:1	DATE:	2014/08/18
		DRW BY:	Huangmei
		CHK BY:	Carl Hu
		APP BY:	
		DRAWING NO.:	C05-015