



No. of Contact	A±0.25	B±0.13	C±0.38	D±0.13	E±0.25
15	16.33	24.99	33.98	39.58	33.98
26	24.66	33.32	42.30	47.90	42.30
44	38.38	47.04	56.02	61.62	55.92

Voltage current rating: 5A
 Contact resistance: 15mΩ Max
 dielectric withstanding voltage: 1000V AC
 Insulation resistance: 5GΩ Min.
 Temperature range: -45°C to +105°C
 Waterproof rating: IP67
 ROHS compliant
 Part number:

BA4-0XX4115D-02

No. of contact: _____
 15: 15pin
 26: 26pin
 44: 44pin

6	Epoxy sealant	Epoxy	
5	O-ring	Silicone	
4	Rear shell	SPCC	Plating: Sn
3	Front shell	SPCC	Plating: Ni
2	Housing	PBT+30%GF	Color: black
1	Terminal	Copper alloy	Plating: full Au 1u"
Item	Desc.	Material	Remark

△			
△			
△	2025/03/24	First edition release	Carl Hu
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□:	☒:	x.	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C		

NAME:	Waterproof HD.D-SUB female solder, machined pin			PART NO.	BA4-0XX4115D-02		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2025/03/24	Huangmei	Carl Hu		BA4-013

lineconn 东莞市林诚塑胶电子有限公司 <http://www.lineconn.com>
 TEL: 0769-85181660 85181770

8

7

6

5

4

3

2

1

F

F

E

E

D

D

C

C

B

B

A

A

8

7

6

5

4

3

2

1