



PCB layout

Current rating: 5 AMP.
 Contact resistance: 30mΩ MAX
 Withstanding voltage: 1000V AC
 Insulation resistance: 5000MΩ Min.
 Temperature range: -45℃ to +105℃
 Degree of protection: IP67
 ROHS compliant
 Part number:



BA4-078811XN-02

Terminal plating:
 4: Full Au 2u"
 5: Full Au 1u"



6	Epoxy sealant	Epoxy	
5	O-ring	Silicone	
4	Rear shell	SPCC	Plating: Sn
3	Front shell	SPCC	Plating: Ni
2	Housing	PBT+30%GF	Color: black
1	Terminal	Copper alloy	Plating: see part number
Item	Desc.	Material	Remark

△	2025/09/12	First edition release	Jack Chen
SIDE	DATE	DESCRIPTION	APPROVER
8	7	6	5

QUALITY SYMBOLS		Tolerance	
□:	☒:	x.	±0.60
CRITICAL	MAJOR	.x	±0.40
▽:	▽:	.xx	±0.25
ZERO DEFECT	S.P.C	 	

NAME:	Waterproof HD,D-SUB 78pin female vertical for PCB,machined pin			PART NO.	BA4-078811XN-02		
REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
SCALE:	N:1	DATE:	2025/09/12	Huangmei	Jack Chen		BA4-024
 东莞市林诚塑胶电子有限公司				http://www.lineconn.com TEL:0769-85181660 85181770			
8	7	6	5	4	3	2	1