



Current rating: 5A
 Withstanding voltage: 500V AC
 Insulation resistance: >1000 mΩ/Min
 Contact resistance: 30mΩ/Max
 Operation temperature: -55°C~+125°C
 ROHS compliant
 Part number:
 B17-C143X1AF-02
 Housing color: _____
 1: black
 6: blue

5	Cable clipper	SPCC	Plating: Ni
4	SR	Rubber	Color: color
3	Housing	PBT+30%G.F.(UL 94V-0)	Color: see part no.
2	Shell	SPCC	Plating: Ni
1	Terminal	Copper alloy	Contact area: G/F Solder area: Sn Under-plating: Ni
Item	Desc.	Material	Remark

A	△	2023/05/29	Change size	Carl Hu	QUALITY SYMBOLS □: ⊠: CRITICAL MAJOR ▽: ▽: ZERO DEFECT S.P.C	Tolerance		NAME:	Centronics(57) 14pin traditional male solder,with 30 metal hood			PART NO.	B17-C143X1AF-02		
	△	2022/11/08	Added 14pin independent drawing	Jack Chen		x.	±0.60	REV:	E	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
	△	2014/09/21	First edition release	Jing Li		.x	±0.40	SCALE:	N:1	DATE:	2014/09/21	Huangmei	Carl Hu		B17-055
	SIDE	DATE	DESCRIPTION			APPROVER	.xx	±0.25	东莞市林诚塑胶电子有限公司			http://www.lineconn.com TEL:0769-85181660 85181770			
	8	7	6	5	4	3	2	1							