



Panel size

Current rating: 10A
 Operating voltage: 125V
 Contact resistance: 5mΩ/Max.
 Durability: 1000 cycles
 Temperature range: -25°C to +85°C
 ROHS compliant

Item	Desc.	Material	Remark
7	Retaining ring	Stainless Steel	
6	Terminal	Copper	Plating: Au
5	Nut	Copper	Plating: Ni
4	Washer	Stainless Steel	
3	Sealing ring	Silicone	
2	Housing	PPS	Color: black
1	Shell	Zinc alloy	Plating: Ni

				QUALITY SYMBOLS		Tolerance		NAME: LF10WBR-4P male solder rear lock panel		PART NO. B10-0LF10WBR-4P		
				□: CRITICAL	☒: MAJOR	x. ±0.60	REV: A	UNIT: mm	DRW BY: Huangmei	CHK BY: Carl Hu	APP BY: []	DRAWING NO. B10-178
A		△	2023/07/19	First edition release		Carl Hu	SCALE: N:1	DATE: 2023/07/19				
SIDE	DATE	DESCRIPTION		APPROVER		ZERO DEFECT	S.P.C.		lineconn 东莞市林诚塑胶电子有限公司		http://www.lineconn.com TEL:0769-85181660 85181770	
8	7	6	5	4	3	2	1					