



Pin No.	A	B	C±0.38
15	16.30	24.99	39.70
26	24.60	33.32	47.60
44	38.00	47.04	61.80

Current rating: 5A
 Withstanding voltage: 1000V AC
 Insulation resistance: 1000MΩ Min.
 Temperature range: -55°C to +105°C
 Waterproof rating: IP67
 ROHS compliant
 Part number: BA4-0XX418XD-A2
 No. of contact: _____
 15: 15pin
 26: 26pin
 44: 44pin
 Terminal plating: _____
 4: Full Au 2u"
 5: Full Au 1u"

Item	Desc.	Material	Remark
6	Glue	Glue	Color: black
5	Waterproof ring	Rubber	Color: Blue
4	Cover	PBT+30%GF	Color: black
3	Housing	PBT+30%GF	Color: black
2	Shell	Zinc alloy	Plating: Ni
1	Terminal	Copper alloy	Plating: see part no.

△				QUALITY SYMBOLS	Tolerance	NAME:	HD.D-SUB machined pin female solder, zinc alloy shell			PART NO.	BA4-0XX418XD-A2		
△				□: ☒:	.x ±0.60	REV:	A	UNIT:	mm	DRW BY	CHK BY	APP BY	DRAWING NO.
△	2025/04/08	First edition release	Carl Hu	CRITICAL MAJOR	.x ±0.40	SCALE:	N:1	DATE:	2025/04/08	Huangmei	Carl Hu		BA4-017
SIDE	DATE	DESCRIPTION	APPROVER	▽: ▽:	.xx ±0.25	东莞市林诚塑胶电子有限公司 http://www.lineconn.com TEL: 0769-85181660 85181770							
8	7	6	5	ZERO DEFECT S.P.C									